

DARAY® Technology that's clear to see

Features

- A 205mm diameter reflector with specialised optical coating filters out 90% infrared radiation (heat) from the beam and emulates daylight so that skin tones look natural.
- Halogen Lamp. Specifically designed for high luminosity, accurate focusing and long life.
- A robust polycarbonate diffuser protects the light and gives excellent shadow reduction. It also reduces infrared radiation in the projected beam and enhances the light's appearance.
- Auto-balance suspension arm. State-of-the-art design permits light head of ceiling and wall models to move in any direction (up to 1,600mm radius) with ease and stability.
- Multiple variants. Mobile, wall-mounted and ceiling-mounted versions are all available.
- Variable intensity. All models feature variable intensity control.
- Double-walled housing. Ensures that the light-head is robust and stays at a low temperature.

Specifications

Light intensity	0 - 70,000 lux @ 1m
Colour rendering index	Ra96
Light-field diameter	18 cm
Colour temperature	4,200K
Supply voltage	230V 50/60 Hz
Lamp life	~1,300 h

Products available

SL200HA	DARAY SL200 light-head and suspension arm	These products require an additional mounting option. Please select from the following:
SL200HAMINI	An SL200 with reduced reach for small rooms or low ceilings	

Mounting options

XSC	Ceiling mount, down-tube and variable intensity controller
XSW	Wall mount and variable intensity controller
SL200E	Flush wall fitting (rear cable entry) Note: the SL200E must be installed by a qualified electrician
SL200M*	DARAY SL200 mobile with IEC inlet and flex

* Mobile models are 1600mm high and come with locking castors as standard

Options/accessories

CMDT	Down-tube cover for suspended ceilings
CMC	Ceiling mount cover for conventional ceilings
MSUPS	24V battery backup power system
LB4059	DARAY SL200 halogen bulb capsule 100W (x3)



Auto-balanced suspension arm

State-of-the-art design permits light-head of ceiling and wall models to move in any direction (up to 1,600mm radius) with ease and stability.

Multi-purpose

Ideal for surgery, ophthalmology, OBS delivery operation, diagnostics and gynaecology. Also suitable for use within casualty departments and intensive care units.

BioProtect® handle

Eliminates the need to remove the handle for sterilising in an autoclave.

